

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
21 February 2002 (21.02.2002)

PCT


(10) International Publication Number
WO 02/13737 A1

- (51) International Patent Classification⁷: A61F 5/443, 5/44 (74) Agents: RAFFNSØE, Knud, Rosenstand et al.; International Patent-Bureau, Høje Taastrup Boulevard 23, DK-2630 Taastrup (DK).
- (21) International Application Number: PCT/DK01/00538
- (22) International Filing Date: 14 August 2001 (14.08.2001) (81) Designated States (*national*): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EC, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
PA 2000 01213 15 August 2000 (15.08.2000) DK
- (71) Applicant (*for all designated States except US*): COLO-PLAST A/S [DK/DK]; Høltedam 1, DK-3050 Humlebaek (DK).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): POULSEN, Lars, Bo [DK/DK]; Slotsvej 5B, DK-3000 Helsingør (DK).
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,

[Continued on next page]

(54) Title: A REUSABLE COLLECTING BAG FOR HUMAN BODY WASTES

(57) Abstract: In a reusable collecting bag such as a stoma bag (1) having a narrowed discharge portion (8) including a slit-like discharge opening in the vicinity of its distal end the discharge portion (8) is brought from an open position for emptying the bag through the discharge opening (9) and a closed position of use by folding and unfolding the discharge portion (8) about at least one folding line (24) transverse to the longitudinal direction of the discharge portion (8). To avoid or reduce faecal contamination of the discharge portion (8) in connection with emptying of the bag a series (16, 18) of sequentially peelable stacked protective members (17, 19) is applied to each of two surface sections of the discharge portion (8) adjacent the discharge opening (9).



WO 02/13737 A1



CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

A reusable collecting bag for human body wastes.

The invention relates to a reusable collecting bag for human body wastes comprising a bag member
5 formed by two film blanks with joined edges, an inlet opening provided in one of said film blanks, connecting elements surrounding said inlet opening for connection of the bag to a body orifice, a narrowed, elongated discharge portion starting at a proximal end
10 at a distance from the inlet opening and extending between two end sections of said film blanks to a distal end, a discharge opening formed in said discharge portion in the vicinity of said distal end, said discharge portion being foldable and unfoldable
15 by at least one folding along a folding line transverse to the longitudinal direction of the discharge portion between said distal and proximal ends to bring the discharge portion from an open unfolded condition to a closed folded condition and
20 vice versa, and a locking device being provided at the discharge portion for locking the bag in said closed folded condition of the discharge portion.

This type of drainable collecting bags are often used as ostomy bags. In the case of ileostomy patients
25 and colostomy patients with uncontrolled release of faeces of a more or less fluid consistence, the collecting bag has to be emptied rather frequently, and the discharge portion thus has to be easy to open and re-close after emptying and at the same time
30 provide a reliable and tight seal in operation, ie. between emptyings.

Several different designs of closure devices have been developed and are generally known.

For instance, GB patent applications Nos. 2 268
35 065 and 2 000 683 disclose collecting bag with closure

devices, in which strips of the interlocking-elements type, such as Velcro®, are placed on each of the film blanks of the discharge portion and which after folding the discharge portion tightly are brought into
5 contact with each other.

Further designs are shown in EP patent application No. 0 013 109, in which the outlet portion is folded and subsequently tucked into a gap formed by a semi-rigid strip attached to the bag wall, as well
10 as published international patent application WO 99/25278, in which the locking means comprises an adhesive layer applied to at least one of two contact surfaces on the discharge portion designed to be brought into contact with each other upon folding of
15 the discharge portion towards the closed position. .

Other types of closure device are disclosed in US patent No. 4,988,343 and published international patent applications Nos. WO 96/19164 and WO 99/66859, in which the discharge portion is rolled up on a locking
20 clip fastened to one of the film blanks.

All of the above-mentioned prior art devices suffer, however, from the common disadvantage that at each emptying or discharge of the faecal or urine content of the bag contamination of the surface parts
25 of the discharge portion adjacent to the discharge opening is hardly avoidable and that consequently washing or cleaning of such surface parts is necessary prior to reclosing of the discharge portion. Evidently such a cleaning operation is not only highly
30 inconvenient and unpleasant to perform, but makes the handling of the bag cumbersome and causes severe problems in particular for users having reduced dexterity.

On this background, it is the object of the
35 present invention to provide a reusable collecting bag

of the kind defined, by which the drawback and handling inconvenience of the prior art devices has been eliminated or at least significantly reduced.

According to the invention, this object is
5 achieved by a reusable collecting bag of the kind defined, which is characterized in that a series of stacked, sequentially peelable adhesive protective members is applied to each of two surface sections of the discharge portion at either side of the discharge
10 opening.

By covering the surface sections of the discharge portion adjacent to the discharge opening with such series of stacked, sequentially peelable protective members the contamination resulting from emptying the
15 bag may be easily removed by peeling off the outermost of the stacked protective members to expose a non-contaminated surface area adjacent to the discharge opening.

Preferred and advantageous embodiments of the
20 reusable collecting bag are stated in the dependent claims.

As will appear therefrom and from the following description the series of peelable protective members according to the invention may be applied to different
25 designs of the bag discharge portion with different locations of the discharge opening and different forms and locations of the locking means.

By itself the application of a series of stacked sequentially peelable, adhesive members to a surface
30 part of a reusable article is known in the art, e.g. from EP patent No. 0 276 043 disclosing the application of such an arrangement of adhesive devices to the attachment of an ostomy bag to a body-attachable pad.

35 In the following the invention will be described

in further detail with reference to the schematic drawings, in which

Fig. 1 shows a plan view of an embodiment of a reusable collecting bag according to the invention,
5 seen from the side intended to face away from the user and in the fully open position;

Fig. 2 shows a longitudinal section of the collecting bag along the line II-II in Fig. 1;

Fig. 3 is a schematic side view diagram of the
10 collecting bag in an intermediate position showing only relevant parts of the bag;

Fig. 4 is a view corresponding to Fig. 1 in the fully closed position of the bag;

Fig. 5 is a diagram corresponding to Fig. 3 of
15 the collecting bag in the fully closed position;

Figs. 6 and 7 are enlarged schematical cross-sectional views of a distal end part of a discharge portion of the bag in an open and closed condition, respectively;

20 Figs. 8 to 12 are views corresponding to Figs. 1 to 4 of a modification of the discharge portion of the collecting bag in Fig. 1; and

Figs. 13 to 15 are views partly corresponding to Figs. 1, 2 and 4 of a further embodiment.

25 In Figs. 2, 3, 4, 9, 10 and 11 some sectional areas are indicated by fully drawn lines in order not to impede the clear reading of the drawings.

The collecting bag shown in the drawings is designed as an ostomy bag of a generally known and
30 common type and comprises a bag member 1 formed by two film blanks 2,3 which are joined along their edges by means of a seam 4 made by welding or in any other convenient manner. The film blanks may be made from any suitable flexible plastic sheet or foil material.

35 In the film blank 3, which in use is intended to

face the user and thus forms the back wall of the bag, an inlet opening 5 is provided, which in a manner known *per se* is surrounded by connecting elements 6 for connection of the bag to a body orifice, ie. in this case an intestinal orifice in the form of a so-called stoma in the user's abdominal wall.

As seen in Fig. 2 a comfort layer 7 of another material than the one used for the film blanks may be provided on the back film blank 3. As further explained in the following both of the two film blanks may alternatively be provided with such a comfort layer which may be made of a conventional non-woven tissue material.

At a distance from the inlet opening 5, the bag is designed with a narrowed, elongated discharge portion 8 starting at a proximal or neck end 8a and extending to a distal or terminal end 8b. The discharge portion 8 is formed by end sections 2a and 3a, respectively, of the film blanks 2,3 and is likewise joined along opposed side edges 8c and 8d.

A short distance from the distal end 8b of the discharge portion 8, a discharge opening 9, through which the bag may be emptied of its contents, is formed as a slit between the distal end edge of the end section 2a of the front film blank 2 and an extreme end part 3b of the end section 3a of the back film blank 3 as further explained in the following.

In order to bring the bag from the open or discharge position shown in Figs. 1 and 2 to a position of use, in which the bag is closed, the collecting bag comprises locking means, which in the embodiment shown comprises foldable locking strips 12 and 13 projecting from the side edges 8c and 8d of the discharge portion 8 at the proximal end 8a thereof. The projecting foldable locking strips 12 and 13,

which may be formed integrally with one of the film blanks 2,3, may comprise male snap fastening members, VELCRO® closure members, different types of adhesive members etc. and are realisable engageable with a
5 second mating locking means 14 and 15 provided on the back film blank 3. It should be noted that the locking device may be designed in other ways, e.g. as a traditional locking clip.

In the embodiment shown in figs. 1 to 5, a first
10 series 16 of stacked, sequentially peelable adhesive protective members 17 is applied to the surface of the extreme end part 2b of the end section 2a of the front film blank 2 immediately adjacent the end edge of end section 2a limiting the discharge opening 9. Likewise
15 a second series 18 of stacked, sequentially peelable adhesive protective members 19 is applied to the surface of the extreme end part 3b of the end section 3a of the back film blank 3.

In the illustrated embodiment, each series 16 and
20 18 of protective members includes, as more clearly shown in figs. 6 and 7, three stacked strip or tape like members 17 and 19, respectively, held together by intermediate layers 20 and 21, respectively, of an adhesive permitting easy sequential peel-off of a
25 single protective member at a time.

The protective strip or tape members 17 and 19 may be made of any suitable material known in the art for removable surface protective members. A preferred material would be a plastic film material providing
30 sufficient protective sealing against penetration of faecal contamination, such as polyethylene or polypropylene. In a further preferred embodiment the protective strip or tape members are made from materials, which are water soluble or easily
35 degradable, such that protective members peeled off

from the bag can be easily disposed of, e.g. by being thrown into a toilet, without presenting any environmental problem. Such protective members could be composed e.g. of an easily degradable non-woven sheet material such as sanitary paper with a water soluble adhesive applied to the side contacting an underlying protective member and a thin sealing layer applied to the external side.

To allow easy peeling-off of the outermost protective member 17 or 19 in each of series 16 and 18, each of the stacked protective members 17 and 19 may, as shown in fig. 1, be provided with a gripping flap 22 and 23, respectively. In the embodiment shown in fig. 1 the gripping flaps project beyond the side edges of the projective members 17 and 19, which are parallel to the discharge slit 9, so as not to impede with the locking function of strips 12 and 13, but they may also be provided at other side edges of the protective members.

The sequence of operations required to bring the collecting bag from the open discharge position shown in fig. 1 towards the fully closed position of use is illustrated in figs. 2 to 5.

Although the application of the series 16 and 18 of protective members may add some increased rigidity to the extreme end parts 2b and 3b, respectively, of end sections 2a and 3a, the first step will as illustrated in figs. 2 and 3 comprise folding of the extreme end part 3b of end section 3a about a folding line 24, which in this case coincides with the discharge slit 9 in a direction such that the series 16 and 18 of protective members 17 and 19 face each other. Subsequently, the thus folded end parts 2b and 3b may be folded, as illustrated in fig. 4 by two subsequent foldings about second folding lines 25 and

26 to bring the discharge portion 8 to a completely folded position permitting locking of the bag in the closed position by engagement of locking strips 12 and 13 with locking means 14 and 15 as shown in fig. 5.

5 When emptying of the bag is required, the sequence of operations needed to bring the bag from the closed position of use shown in fig. 5 to the open discharge position shown in fig. 1 is the opposite. After release of the engagement between locking strips
10 12, 13 and locking means 14, 15 the discharge portion 8 is unfolded and the faecal content of the bag is emptied through the discharge opening 9. After emptying the bag the outermost protective strip member 17 and 19 in each of series 16 and 18 is peeled-off to
15 expose the clean surfaces of the underlying strips 17 and 19 adjacent to the discharge opening, before the discharge portion 8 is folded back towards its closed position.

 The number of protective members in each of
20 series 16 and 18 will thus depend on the envisaged number of reuses of the bag. Typically, a number of stacked members will be provided in each of series 16 and 18, which will allow 24 hours use of the bag without replacement, e.g. from 3 to 5 stacked members,
25 whereas in order to avoid difficulties in handling of the discharge portion in connection with the unfolding and unfolding thereof, the number would preferably not increase eight stacked members,

 In the embodiment illustrated in figs. 8 to 12
30 the collection part of the bag is, in principle, of the same design as shown in fig. 1 to 5 and only the discharge portion 27 and the folding and unfolding thereof for closing and opening of the bag will be further described.

35 Also in this case, the discharge portion 108

comprises a number of foldable sections. At the proximal end of the discharge portion 108 foldable sections 110 and 111 are formed, of which the former is arranged between two folding lines 112 and 113 and the latter between folding line 112 and a limiting line 114. The foldable sections 110 and 111 are provided with a carrier plate 115, typically made of a foam material, which is fastened to the front film blank 102.

10 As illustrated in figs. 9 and 10, in a first folding step during closing of the bag the discharge portion 108 is folded about folding line 112 to bring the surface parts of the carrier plate 115 fastened to sections 110 and 111, respectively, into mutual
15 surface contact. To hold the discharge portion 108 in this first folded position, one of the surface parts of the carrier plate 115, e.g. the surface part applied to section 111 is provided with a layer 116 of an adhesive capable of easy release and repeated
20 adhesion.

In the discharge portion 108 the discharge opening 109 is provided in the same way as described for the embodiment in figs. 1 to 5 as a slit-like opening between the end edge of an extension 102a of front film blank 102 and an extreme end part 103b of an extension 103a of the back film blank 103. On
25 either side of the slit-like discharge opening 109 first and second series 117 and 118 of stacked, sequentially peelable adhesive protective members are applied to the extreme ends part 102b and 103b,
30 respectively, of the extensions 102a and 103a of the front and back film blanks. The two series 117 and 118 of protective members may, in principle be designed and composed as described above for the embodiment in
35 figs. 1 to 5.

As illustrated in fig. 10 the extreme end parts 102b and 103b of the film blank extension 102a and 103a are, in this case not folded with respect to each other, but provide a contact surface 119 for use in a subsequent folding operation, in which the distal end of the discharge portion 108 comprising the extreme end parts 102b and 103b is folded, as shown in fig. 11, about the folding line 114 in the same folding direction as the first folding about folding line 112.

10 By this subsequent folding the contact surface 119 provided by the outermost protective member in series 117 and 118 is brought into contact with a contact surface 120 provided by a flap element 121 fastened to the front film blank 102 and comprising a flexible flap portion 122, which is foldable about a folding line 123.

The discharge portion 108 may be kept in the position occupied after the subsequent folding operation by an adhesive layer 124, which is capable of repeated releases and adhesions and may conveniently be applied to the contact surface 120 provided by the flap element 121. Alternatively, such an adhesive layer may also be provided, however by the contact surface 119 provided by the outermost protective member in series 117 and 118.

20 After the subsequent folding to the position shown in fig. 11 the flap portion 122 is folded about folding line 123 and brought onto contact with a contact surface 125 provided by the back film blank 103 at the proximal section 10 of the discharge portion 108.

The function and handling of the series 117 and 118 of protective members may be the same as explained for the embodiment in figs. 1 to 5.

35 A still further embodiment is shown in figs. 13

to 15, in which the discharge opening 209 is provided between the extreme ends of extension 202a and 203a of the front and back film blanks 202 and 203, respectively, of the bag 201, in which the inlet
5 opening 205 in the back film blank 293 is surrounded in this embodiment by a conventional adhesive fixing plate 206. The locking means comprises a strip member 212 firmly connected with the extension 202a of the front film blank 202 at the extreme end thereof.

10 Such a locking strip is known per se from international patent application WO 96/19164 and comprises a central part 213 adhesively connected with the extension 202a and end sections formed integrally therewith vis folding sections 213a and 213b.

15 In this case the two series 216 and 218 of peelable, stacked protective members are applied to the external side of the part of the locking strip 212 connected with the extension 202a of the front film blank 202 and the external side of the extension 203a
20 of the back film blank 203. From the cross sectional view in fig. 14 it will readily appear that folding of the discharge portion 208 from the open position in fig. 13 to the closed position of use shown in fig. 15 is effected by folding the discharge portion 208 from
25 the extreme ends of bag extensions 202a and 203a limiting the discharge opening 209 about the locking strip 212. The function of the peelable protective members in each of series 216 and 218 is the same as described above for the embodiments in figs. 1 to 5.

30 As will appear to those skilled in the art the protection of the discharge portion offered by the invention is not limited to the embodiments described in the foregoing, but may be applied to various designs of reusable stoma bags comprising a foldable
35 discharge portion including, in particular the bag

12

designs disclosed in GB 2 000 683 A, US 4,988,343, WO
96/19164 and WO99/66859. The disclosure of the latter,
which is incorporated herein by reference, comprises a
bag discharge portion provided with resilient sealing
5 plates to improve the sealing of the discharge portion
in its closed position. Combined therewith the
provision of peelable protective members according to
the invention provides the additional advantage of
protection of such sealing plates against faecal
10 contamination.

15

20

25

30

35

P A T E N T C L A I M S

1. A reusable collecting bag for human body
5 wastes comprising a bag member (1,101,201) formed by
two film blanks (2,3; 102,103; 202,203) with joined
edges, an inlet opening (5,105,205) provided in one
(3,103,203) of said film blanks, connecting elements
(6,106,206) surrounding said inlet opening for
10 connection of the bag to a body orifice, a narrowed,
elongated discharge portion (8,108,208) starting at a
proximal end at a distance from the inlet opening
(5,105,205) and extending between two end sections
(2a,3a; 102a,103a; 202a,203a) of said film blanks to a
15 distal end, a discharge opening (9,109,209) formed in
said discharge portion (8,108,208) in the vicinity of
said distal end, said discharge portion (8,108,208)
being foldable and unfoldable by at least one folding
along a folding line (24,112) transverse to the
20 longitudinal direction of the discharge portion
between said distal and proximal ends to bring the
discharge portion from an open unfolded condition to a
closed folded condition and vice versa, and a locking
means (10 - 13; 119,120, 112) for locking the
25 discharge portion in said closed folded condition
thereof, c h a r a c t e r i z e d in that a series
(16,18; 117,118; 216,218) of stacked, sequentially
peelable adhesive protective members (17,19) is
applied to each of two surface sections of the
30 discharge portion (8,108,208) at either side of the
discharge opening (9,109,209).

2. A reusable collecting bag as claimed in claim
1, c h a r a c t e r i z e d in that the discharge
opening (9,109) is formed between one (3,103) of said
35 two end sections of the film blanks and an end edge of

the other end section (2,102) as a slit and that said series (16,18; 117,118) of protective members are applied to surface sections of said end sections (2A,3A;102a,103a) adjoining the end edge of said other
5 end section (3a,103a).

3. A reusable collecting bag as claimed in claim 2, c h a r a c t e r i z e d in that the locking means comprises a locking strip (216) formed integrally with said one end section (202a) adjacent to the discharge
10 opening (209) and that one of said series (216) of protective members is applied to the locking strip.

4. A reusable collection bag as claimed in claim 1, c h a r a c t e r i z e d in that said discharge opening (209) is formed as a slit between end edges of
15 both of said end sections (202a,203a) and that said series (216,218) of protective members are applied to external surface sections of each of said end sections (202a,203a) adjacent to said slit.

5. A reusable collecting bag as claimed in any of
20 the preceding claims, c h a r a c t e r i z e d in that the locking means comprises an adhesive layer (124) applied to at least one (120) of two contact surfaces (119, 120) intended to be brought into contact with each other upon folding of the discharge
25 portion (208) towards the closed position.

6. A reusable collecting bag as claimed in claim 5, c h a r a c t e r i z e d in that said one contact surface (119), to which an adhesive layer is applied, comprises the side of each of said protective members
30 in at least one of said series (117,118) facing away from the end section (102a,103a) of the discharge portion (108), to which said one series is applied.

7. A reusable collection bag as claimed in any of the preceding claims, c h a r a c t e r i z e d in
35 that the protective members (17,19) in each of said

series (16,18) are formed as strip members applied to said surface section to extend transverse to the longitudinal direction of the discharge portion (8).

8. A reusable collection bag as claimed in claim 5 7, characterized in that each protective member (17,19) in each of said series (16,18) is formed with a gripping flap (22,23) extending beyond a side edge of the protective member (17,19).

9. A reusable collecting bag as claimed in any of 10 the preceding claims, characterized in that each of said series (16,18) comprises from 2 to 8 of said stacked protective members (17,19).

10. A reusable collecting bag as claimed in any of the preceding claims, characterized in 15 that said series of stacked peelable protective members are applied to resilient sealing plates connected with said surface sections of the discharge portion.

11. A reusable collecting bag as claimed in any 20 of the preceding claims, characterized in that the protective strip or tape members are made from materials, which are water soluble or easily degradable.




FIG. 1




FIG. 2




FIG. 3




FIG. 5




FIG. 4




FIG. 6





FIG. 7






FIG. 13




FIG. 15




FIG. 14

PCT/DK 01/00538

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 A61F5/443 A61F5/44

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 IPC 7 A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 276 042 A (CRAIG MED PROD LTD) 27 July 1988 (1988-07-27) column 6, line 28 - line 41; figures 6-11	1
A	US 4 753 703 A (JENSEN OLE R) 28 June 1988 (1988-06-28) abstract; figures 1,2	1
A	WO 99 66859 A (COLOPLAST AS) 29 December 1999 (1999-12-29) cited in the application abstract; figures	1
A	US 5 968 024 A (FREEMAN FRANK) 19 October 1999 (1999-10-19)	
A	US 4 460 359 A (FENTON LEONARD) 17 July 1984 (1984-07-17)	

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *Z* document member of the same patent family

Date of the actual completion of the international search

15 October 2001

Date of mailing of the international search report

23/10/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5618 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Sánchez y Sánchez, J

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0276042	A	27-07-1988	GB 2157567 A	30-10-1985
			AT 50488 T	15-03-1990
			AT 72957 T	15-03-1992
			AT 72958 T	15-03-1992
			AT 71824 T	15-02-1992
			AU 581419 B2	23-02-1989
			AU 3650384 A	27-06-1985
			CA 1264134 A1	02-01-1990
			DE 3481402 D1	05-04-1990
			DE 3485482 D1	05-03-1992
			DE 3485548 D1	09-04-1992
			DE 3485549 D1	09-04-1992
			DK 83391 A	06-05-1991
			DK 608184 A	20-06-1985
			EP 0146367 A2	26-06-1985
			EP 0276042 A2	27-07-1988
			EP 0276043 A2	27-07-1988
			EP 0276898 A2	03-08-1988
			GB 2151482 A ,B	24-07-1985
			GB 2153232 A ,B	21-08-1985
			IE 56218 B1	22-05-1991
			JP 1819047 C	27-01-1994
			JP 5024781 B	08-04-1993
			JP 60156457 A	16-08-1985
			JP 1947715 C	10-07-1995
			JP 6070950 A	15-03-1994
			JP 6071470 B	14-09-1994
			NO 845081 A ,B,	20-06-1985
			NZ 210518 A	08-01-1988
			US 4701169 A	20-10-1987
			ZA 8409643 A	31-07-1985
			GB 2162626 A ,B	05-02-1986
US 4753703	A	28-06-1988	AT 68685 T	15-11-1991
			AU 600969 B2	30-08-1990
			AU 7770387 A	14-04-1988
			CA 1294504 A1	21-01-1992
			DE 3774065 D1	28-11-1991
			DK 525487 A	09-04-1988
			EP 0263625 A2	13-04-1988
			ES 2025669 T3	01-04-1992
			GR 3003603 T3	16-03-1993
			IE 61625 B	16-11-1994
			JP 2604756 B2	30-04-1997
			JP 63102755 A	07-05-1988
			US 4894058 A	16-01-1990
WO 9966859	A	29-12-1999	DK 80498 A	20-12-1999
			AU 736203 B2	26-07-2001
			AU 4359699 A	10-01-2000
			CN 1306408 T	01-08-2001
			WO 9966859 A2	29-12-1999
			EP 1087723 A2	04-04-2001
US 5968024	A	19-10-1999	NONE	
US 4460359	A	17-07-1984	NONE	